

16K CMOS Static RAM (2048x8) 24PIN 6116

型名	社名	温度範囲 (℃)	スイッチング特性										電 源		入 力 [*typ]				出 力 [*typ]		備 考	
			TAAC max (ns)	TCAC max (ns)	TOE max (ns)	T <sub>OH</sub> min (ns)	T <sub>OD</sub> max (ns)	T <sub>WP</sub> min (ns)	T <sub>DS</sub> min (ns)	T <sub>DH</sub> min (ns)	T <sub>WD</sub> min (ns)	T <sub>WR</sub> max (ns)	VDD or VCC (V)	I <sub>DD</sub> max (mA)	I <sub>DD</sub> STANDBY (I <sub>SB</sub> /I <sub>SB2</sub> ) (mA)	V <sub>IL</sub> max (V)	V <sub>IH</sub> min (V)	C <sub>i</sub> max (pF)	V <sub>OL</sub> /I <sub>VOL</sub> max (V/mA)	V <sub>OH</sub> /I <sub>VOH</sub> min (V/mA)		C <sub>o</sub> max (pF)
LC3516A/AM/AS-12	SANYO	-30~85	120	120		5		95	60	0	0	10	4.5~5.5	80	3.0/0.03	0.8	2.2	10	0.4/2.0	2.4/1.0	10	
LC3516A/AM/AS-15	SANYO	-30~85	150	150		5		120	70	0	0	10	4.5~5.5	80	3.0/0.03	0.8	2.2	10	0.4/2.0	2.4/1.0	10	
LC3516AD/ASD/AMD	SANYO	-20~70	2000	2000		0		1500	1000	100	100	100	2.6~5.5	80	5.0/0.005	0.5	1.6	10	0.2/0.2	2.4/0.1	10	
LC3516AL/AML/ASL-10	SANYO	-30~85	100	100		5		75	50	0	0	10	4.5~5.5	80	3.0/0.001	0.8	2.2	10	0.4/2.0	2.4/1.0	10	
LC3516AL/AML/ASL-12	SANYO	-30~85	120	120		5		95	60	0	0	10	4.5~5.5	80	3.0/0.001	0.8	2.2	10	0.4/2.0	2.4/1.0	10	
LC3516AL/AML/ASL-15	SANYO	-30~85	150	150		5		120	70	0	0	10	4.5~5.5	80	3.0/0.001	0.8	2.2	10	0.4/2.0	2.4/1.0	10	
LC3518B/BM/BS-12	SANYO	-30~85	120	120		20	40	100	60	0	0	0	4.5~5.5	15	3.0/0.03	0.8	2.2	10	0.4/2.0	2.4/1.0	5	
LC3518B/BM/BS-15	SANYO	-30~85	150	150		20	50	120	70	0	0	0	4.5~5.5	15	3.0/0.03	0.8	2.2	10	0.4/2.0	2.4/1.0	5	
LC3518BL/BML/BSL-12	SANYO	-30~85	120	120		20	40	100	60	0	0	0	4.5~5.5	15	3.0/0.001	0.8	2.2	10	0.4/2.0	2.4/1.0	5	
LC3518BL/BML/BSL-15	SANYO	-30~85	150	150		20	50	120	70	0	0	0	4.5~5.5	15	3.0/0.001	0.8	2.2	10	0.4/2.0	2.4/1.0	5	
LH5115-55	SHARP	0~70	55	55	20	5	20	20	15	10	0	10	4.5~5.5	60	-/0.01	0.8	2.2	5	0.4/4	2.4/2.3	10	
LH5115-70	SHARP	0~70	70	70	25	5	20	20	15	10	0	10	4.5~5.5	60	-/0.01	0.8	2.2	5	0.4/4	2.4/2.3	10	
LH5116-15	SHARP	0~70	150	150	75	15	40	110	70	10	0	20	4.5~5.5	40	-/0.01	0.8	2.2	5	0.4/2.1	2.4/1	8	
LH5116-20	SHARP	0~70	200	200	100	20	60	140	80	10	5	35	4.5~5.5	40	-/0.01	0.8	2.2	5	0.4/2.1	2.4/1	8	
LH5116SN	SHARP	0~50	1000	1000	100	10	40	100	50	20	0	20	2.7~3.3	10	1/-	0.8	2.2	7	0.5/2.1	2.2/1	10	
LH5116-10	SHARP	0~70	100	100	40	10	40	60	30	10	0	10	4.5~5.5	30	1/-	0.8	2.2	7	0.4/2.1	2.4/1	10	
MSM5116P	MITSUBISHI	0~70	200										5	50	0.015/-							
MSM5116P-12	MITSUBISHI	0~70	120										5	50	0.015/-							
MSM5116P-15	MITSUBISHI	0~70	150										5	50	0.015/-							
MB8416-15	FUJITSU	-40~85	150		75	15	50	110	50	0	0		4.5~5.5	60	2/0.01	0.8	2.2	7	0.4/4	2.4/1	10	
MB8416-20	FUJITSU	-40~85	200		100	0	60	140	60	0	0		4.5~5.5	60	2/0.1	0.8	2.2	7	0.4/4	2.4/1	10	
MB8416-20L	FUJITSU	-40~85	200		100	0	60	140	60	0	0		4.5~5.5	60	2/0.001	0.8	2.2	7	0.4/4	2.4/1	10	
MB8416A-12	FUJITSU	-40~85	120		50	15	40	70	40	0	0		4.5~5.5	60	2/1	0.8	2.2	7	0.4/4	2.4/1	10	
MB8416A-12L	FUJITSU	0~70	120		50	15	40	70	40	0	0		4.5~5.5	60	1/0.05	0.8	2.2	7	0.4/4	2.4/1	10	
MB8416A-15	FUJITSU	-40~85	150		60	15	50	90	40	0	0		4.5~5.5	60	2/1	0.8	2.2	7	0.4/4	2.4/1	10	
MB8416A-15L	FUJITSU	0~70	150		60	15	50	90	40	0	0		4.5~5.5	60	1/0.05	0.8	2.2	7	0.4/4	2.4/1	10	
MC65116-12	MOTOROLA	0~70	120		80	10	40	70	35	5	20		4.5~5.5	55	10/0.1	0.8	2.2	10	0.4/2	2.4/1	10	
MC65116-15	MOTOROLA	0~70	150		100	15	50	90	40	10	20		4.5~5.5	55	10/0.1	0.8	2.2	10	0.4/2	2.4/1	10	
MC65116-20	MOTOROLA	0~70	200		120	15	60	120	60	10	20		4.5~5.5	55	10/0.1	0.8	2.2	10	0.4/2	2.4/1	10	
MC65116-12	MOTOROLA	0~70	120		80	10	40	70	35	5	20		4.5~5.5	55	10/2	0.8	2.2	5	0.4/4	2.4/1	7	
MC65116-15	MOTOROLA	0~70	150		100	15	50	90	40	10	20		4.5~5.5	55	10/2	0.8	2.2	5	0.4/4	2.4/1	7	
MC65116-20	MOTOROLA	0~70	200		120	15	60	120	60	10	20		4.5~5.5	55	10/2	0.8	2.2	5	0.4/4	2.4/1	7	
MK48202-15	MOSTEK	0~70	150		55	15	35	90	40	0	0		4.75~5.25	80	3/1	0.8	2.2		0.4/2.1	2.4/1	1	WITH LITHIUM BATTERY
MK48202-20	MOSTEK	0~70	200		65	15	40	120	60	0	0		4.75~5.25	80	3/1	0.8	2.2		0.4/2.1	2.4/1	1	WITH LITHIUM BATTERY
MK48202-25	MOSTEK	0~70	250		75	15	50	150	100	0	0		4.75~5.25	80	3/1	0.8	2.2		0.4/2.1	2.4/1	1	WITH LITHIUM BATTERY
MN4416-10	MATSUSHITA	0~70	100		100	5	40	70	40	5	5		4.5~5.5	35	3/-	0.8	2.2	5	0.4/2.1	2.4/1	10	
MN4416-12	MATSUSHITA	0~70	120		120	10	40	80	40	5	5		4.5~5.5	35	3/-	0.8	2.2	5	0.4/2.1	2.4/1	10	
MN4416S-12	MATSUSHITA	0~70	120		120	5	40	80	40	5	5		4.5~5.5	35	20/0.2	0.8	2.2	5	0.4/2.1	2.4/1	10	
MN4416S-15	MATSUSHITA	0~70	150		150	10	50	90	40	10	10		4.5~5.5	35	20/0.2	0.8	2.2	5	0.4/2.1	2.4/1	10	
MS6515L-10	MOSEL	0~70	100	100	50	5	40	50	30	0	0	0	4.5~5.5	90	2/0.01	0.8	2.2	8	0.4/4	2.4/1	10	
MSM5126-20RS	OKI	-30~85	200		200	10	80	150	80	0	0	0	4.5~5.5	70	3/0	0.8	2.2	10	0.4/2	2.4/1	10	EQUIVALENT TO TC5117
MSM5126-25RS	OKI	-30~85	250		250	10	80	200	120	0	0	0	4.5~5.5	70	3/0	0.8	2.2	10	0.4/2	2.4/1	10	