

# IRF7328PbF



HEXFET® Power MOSFET

- Trench Technology
- Ultra Low On-Resistance
- Dual P-Channel MOSFET
- Available in Tape & Reel
- Lead-Free

| $V_{DSS}$   | $R_{DS(on) \text{ max}}$ | $I_D$ |
|-------------|--------------------------|-------|
| <b>-30V</b> | 21mΩ @ $V_{GS} = -10V$   | -8.0A |
|             | 32mΩ @ $V_{GS} = -4.5V$  | -6.8A |

## Description

New trench HEXFET® Power MOSFETs from International Rectifier utilize advanced processing techniques to achieve extremely low on-resistance per silicon area. This benefit, combined with the ruggedized device design that HEXFET power MOSFETs are well known for, provides the designer with an extremely efficient and reliable device for use in battery and load management applications.



## Absolute Maximum Ratings

|                                | Parameter                                 | Max.         | Units |
|--------------------------------|---|--------------|-------|
| $V_{DS}$                       | Drain-Source Voltage                      | -30          | V     |
| $I_D @ T_A = 25^\circ\text{C}$ | Continuous Drain Current, $V_{GS} @ -10V$ | -8.0         | A     |
| $I_D @ T_A = 70^\circ\text{C}$ | Continuous Drain Current, $V_{GS} @ -10V$ | -6.4         |       |
| $I_{DM}$                       | Pulsed Drain Current <sup>①</sup>         | -32          |       |
| $P_D @ T_A = 25^\circ\text{C}$ | Maximum Power Dissipation <sup>③</sup>    | 2.0          | W     |
| $P_D @ T_A = 70^\circ\text{C}$ | Maximum Power Dissipation <sup>③</sup>    | 1.3          | W     |
|                                | Linear Derating Factor                    | 16           | mW/°C |
| $V_{GS}$                       | Gate-to-Source Voltage                    | ± 20         | V     |
| $T_J, T_{STG}$                 | Junction and Storage Temperature Range    | -55 to + 150 | °C    |


## Thermal Resistance

|                 | Parameter                                | Max. | Units |
|-----------------|--|------|-------|
| $R_{\theta JA}$ | Maximum Junction-to-Ambient <sup>③</sup> | 62.5 | °C/W  |

## Electrical Characteristics @ $T_J = 25^\circ\text{C}$ (unless otherwise specified)

|                                 | Parameter                            | Min. | Typ.   | Max. | Units | Conditions   |
|---------------------------------|--------------------------------------|------|--------|------|-------|--|
| $V_{(BR)DSS}$                   | Drain-to-Source Breakdown Voltage    | -30  | —      | —    | V     | $V_{GS} = 0V, I_D = -250\mu A$                       |
| $\Delta V_{(BR)DSS}/\Delta T_J$ | Breakdown Voltage Temp. Coefficient  | —    | -0.018 | —    | V/°C  | Reference to $25^\circ\text{C}, I_D = -1\text{mA}$   |
| $R_{DS(on)}$                    | Static Drain-to-Source On-Resistance | —    | 17     | 21   | mΩ    | $V_{GS} = -10V, I_D = -8.0A$ ②                       |
|                                 |                                      | —    | 26.8   | 32   |       | $V_{GS} = -4.5V, I_D = -6.8A$ ②                      |
| $V_{GS(th)}$                    | Gate Threshold Voltage               | -1.0 | —      | -2.5 | V     | $V_{DS} = V_{GS}, I_D = -250\mu A$                   |
| $g_{fs}$                        | Forward Transconductance             | 12   | —      | —    | S     | $V_{DS} = -10V, I_D = -8.0A$                         |
| $I_{DSS}$                       | Drain-to-Source Leakage Current      | —    | —      | -15  | μA    | $V_{DS} = -24V, V_{GS} = 0V$                         |
|                                 |                                      | —    | —      | -25  |       | $V_{DS} = -24V, V_{GS} = 0V, T_J = 70^\circ\text{C}$ |
| $I_{GSS}$                       | Gate-to-Source Forward Leakage       | —    | —      | -100 | nA    | $V_{GS} = -20V$                                      |
|                                 | Gate-to-Source Reverse Leakage       | —    | —      | 100  |       | $V_{GS} = 20V$                                       |
| $Q_g$                           | Total Gate Charge                    | —    | 52     | 78   | nC    | $I_D = -8.0A$  |
| $Q_{gs}$                        | Gate-to-Source Charge                | —    | 9.8    | —    |       | $V_{DS} = -15V$                                      |
| $Q_{gd}$                        | Gate-to-Drain ("Miller") Charge      | —    | 8.3    | —    |       | $V_{GS} = -10V$                                      |
| $t_{d(on)}$                     | Turn-On Delay Time                   | —    | 13     | 20   | ns    | $V_{DD} = -15V, V_{GS} = -10.0V$                     |
| $t_r$                           | Rise Time                            | —    | 15     | 23   |       | $I_D = -1.0A$  |
| $t_{d(off)}$                    | Turn-Off Delay Time                  | —    | 198    | 297  |       | $R_G = 6.0\Omega$                                    |
| $t_f$                           | Fall Time                            | —    | 98     | 147  |       | $R_D = 15\Omega$ ②                                   |
| $C_{iss}$                       | Input Capacitance                    | —    | 2675   | —    | pF    | $V_{GS} = 0V$  |
| $C_{oss}$                       | Output Capacitance                   | —    | 409    | —    |       | $V_{DS} = -25V$                                      |
| $C_{rss}$                       | Reverse Transfer Capacitance         | —    | 262    | —    |       | $f = 1.0\text{MHz}$                                  |

## Source-Drain Ratings and Characteristics

|          | Parameter                                 | Min. | Typ. | Max. | Units | Conditions   |
|----------|---|------|------|------|-------|--|
| $I_S$    | Continuous Source Current<br>(Body Diode) | —    | —    | -2.0 | A     | MOSFET symbol showing the integral reverse p-n junction diode.  |
| $I_{SM}$ | Pulsed Source Current<br>(Body Diode) ①   | —    | —    | -32  |       |  |
| $V_{SD}$ | Diode Forward Voltage                     | —    | —    | -1.2 | V     | $T_J = 25^\circ\text{C}, I_S = -2.0A, V_{GS} = 0V$ ②   |
| $t_{rr}$ | Reverse Recovery Time                     | —    | 37   | 56   | ns    | $T_J = 25^\circ\text{C}, I_F = -2.0A$  |
| $Q_{rr}$ | Reverse Recovery Charge                   | —    | 36   | 54   | nC    | $di/dt = -100A/\mu s$ ②  |

### Notes:

① Repetitive rating; pulse width limited by max. junction temperature.

② Pulse width  $\leq 400\mu s$ ; duty cycle  $\leq 2\%$ .

③ Surface mounted on FR-4 board,  $t \leq 10\text{sec}$ .




Fig 1. Typical Output Characteristics




Fig 2. Typical Output Characteristics




Fig 3. Typical Transfer Characteristics






Fig 4. Normalized On-Resistance Vs. Temperature


# IRF7328PbF




**Fig 5.** Typical Capacitance Vs. Drain-to-Source Voltage




**Fig 6.** Typical Gate Charge Vs. Gate-to-Source Voltage




**Fig 7.** Typical Source-Drain Diode Forward Voltage




**Fig 8.** Maximum Safe Operating Area




**Fig 9.** Maximum Drain Current Vs. Case Temperature



**Fig 10a.** Switching Time Test Circuit




**Fig 10b.** Switching Time Waveforms




**Fig 11.** Maximum Effective Transient Thermal Impedance, Junction-to-Ambient

# IRF7328PbF


International  
**IR** Rectifier




**Fig 12.** Typical On-Resistance Vs. Gate Voltage



**Fig 13.** Typical On-Resistance Vs. Drain Current




**Fig 14a.** Basic Gate Charge Waveform



**Fig 14b.** Gate Charge Test Circuit


## SO-8 Package Outline

Dimensions are shown in millimeters (inches)




**NOTES:**

1. DIMENSIONING & TOLERANCING PER ASME Y14.5M-1994.
2. CONTROLLING DIMENSION: MILLIMETER
3. DIMENSIONS ARE SHOWN IN MILLIMETERS (INCHES).
4. OUTLINE CONFORMS TO JEDEC OUTLINE MS-012AA.
5. DIMENSION DOES NOT INCLUDE MOLD PROTRUSIONS. MOLD PROTRUSIONS NOT TO EXCEED 0.15 (.006).
6. DIMENSION DOES NOT INCLUDE MOLD PROTRUSIONS. MOLD PROTRUSIONS NOT TO EXCEED 0.25 (.010).
7. DIMENSION IS THE LENGTH OF LEAD FOR SOLDERING TO A SUBSTRATE.



## SO-8 Part Marking Information (Lead-Free)

EXAMPLE: THIS IS AN IRF7101 (MOSFET)




# IRF7328PbF

International  
**IOR** Rectifier


## SO-8 Tape and Reel

Dimensions are shown in millimeters (inches)



### NOTES:

1. CONTROLLING DIMENSION : MILLIMETER.
2. ALL DIMENSIONS ARE SHOWN IN MILLIMETERS(INCHES).
3. OUTLINE CONFORMS TO EIA-481 & EIA-541.



### NOTES:

1. CONTROLLING DIMENSION : MILLIMETER.
2. OUTLINE CONFORMS TO EIA-481 & EIA-541.

Data and specifications subject to change without notice.  
This product has been designed and qualified for the Consumer market.  
Qualifications Standards can be found on IR's Web site.

International  
**IOR** Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105  
TAC Fax: (310) 252-7903

Visit us at [www.irf.com](http://www.irf.com) for sales contact information.12/2010  
[www.irf.com](http://www.irf.com)